

HYOSUNG

MX8200QT

The future of small footprint, full function, high capacity, recycling ATM is already here.

The future of a small footprint, full function, high capacity, recycling ATM is already here. The **MX8200QT** was designed to not only move more teller transactions to a more cost effective channel but to also fit the changing branch and off premise formats. The **MX8200QT** enables customers to choose how they want to interact with your institution by offering a more robust set of transactions through Hyosung's industry leading core integration; autonomously or with the assistance from branch staff or on demand video assistance.

Features

Highest Availability

Innovative design and the use of Hyosung manufactured core technologies allows for fast, easy replenishment and reduced downtime. The **MX8200QT** is designed to provide reliability that is unequaled in the market, with minimum maintenance and maximum uptime.

Functionality

Delivers transactions via both self-service or video assistance. The small footprint enables a wide variety of placement possibilities including new markets. The **MX8200QT** allows for an unparalleled range of transactions types outside the traditional branch space when deployed with Hyosung's innovative core integrated software and powerful video assistance solutions.

Capacity

MX8200QT offers high capacity, cash recycling capability and multi-check function. High capacity allows for denomination selection.

Innovation

Small, compact footprint cash recycler that can be deployed anywhere. Full function deposit capability enables financial institutions to extend their presence and deliver convenience to consumers. High capacity, cash recycler module creates efficiencies within the cash cycle.



HYOSUNG

MX8200QT

Specifications

Dimensions

- Height: 1,240mm (48.8")
- Width: 503.8mm (19.8")
- Depth: 1,167.3mm (46")
- Weight: 499.9kg (1,102lbs)

Environmental Conditions

- Temperature: 32°F – 104°F (0°C ~ 40°C)
- Humidity 25% – 85%

System Platform

- Microsoft Windows® 10
- Hyosung Moniplus XFS

Customer Interface

- 21" high visibility touch screen (15" or 19" optional)
- PIN Pad – PCI compliant
- ADA audio guidance – earphone jack
- Card Reader – EMV compliant, anti-skimming and anti-shimming included
- Contactless – Integrated reader (via card, smartphone or smartwatch)
- Web camera – includes video camera and microphone (optional)

Media Handling

- **Cash Recycler**
 - 4 Recycling + 1 Deposit cassette
 - Recycle up to 4 denominations with 2,950 notes per recycling cassette, and 2,950 notes in the deposit cassette.*
- **Cash & Check In Module (CSM)**
 - Bundle check deposit
 - Insert bundle 10 checks
 - Total check capacity - 350 checks*
 - Sidecar option - insert bundle 50 checks, total check capacity 2,000 checks*

Security

- Safe – UL291 Level 1
- Alarm – Seismic + Heat
- Locking Device – KABA Mas Cencon
- Sensor – Safety door sensor
- Security – Terminal block for easy security connections
- Camera – CCD: None (cabling only)
- Privacy Filter – 15", 19", and 21.5"

Printer

- 3.1" graphical thermal receipt printer

Servicing

- Front Access
- State of health indicators for all modules

Power Supply

- AC 100V ~ 127V±10%, 200V ~ 240V±10% 50/60Hz

Additional Features

- Communication – TCP/IP
- Backup battery reserves the last transaction & safe shutdown
- Palm vein scanner (optional)
- ID scanner (optional)

*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.